



# TECHNICAL DATA SHEET

PRODUCT:

CERA NATURALE

## DESCRIPTION

**CERA NATURALE** (Natural Wax) is a special water-based dirt protective, for all glossy lime-based mineral finishing:

- glossy plaster in all its range;
- Venetian plaster in all its range.

**CERA NATURALE** is composed by genuine bees wax, pure *savon de Marseille* and additives in an homogeneous blend. It's completely solvent free (0% VOC).

**CERA NATURALE** increases the glossiness and confers to the surface washable properties, maintaining an outstanding breathethrough capacity.

**CERA NATURALE** is suitable for **indoor** wall surfaces protection only.

## APPLICATION

**Ready to use, mix carefully before using.**

Let the surface to dry out for at least **48 hours**.

Apply the wax with a soft (non-abrasive) sponge for 1m<sup>2</sup> (about 11ft<sup>2</sup>) at a time, until the surface has completely absorbed it.

After about 30/40 minutes, polish the surface using a non-woven fabric cloth (micro fibre or *TNT*/tissue-non-tissue cloth).

## STORAGE

The product maintains its properties for a period of 12 months if protected from excessive heat and cold.

The storage temperature must be included between **+5°C** and **+30°C**. **Protect from frost.**

## SAFETY GUIDELINES

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly with water. For more information consult the safety sheet.

## DISPOSAL

The product must be disposed in agreement with current regulations.

Empty containers have to be sent to recycling plants.

## TECHNICAL SPECIFICATIONS

<b>Appearance</b>	dense liquid
<b>Colour</b>	transparent neutral white
<b>Packaging</b>	2Kg
<b>Application tools</b>	soft sponge, non-woven fabric cloth
<b>Specific weight</b>	0,99 ± 0,05Kg/l
<b>pH</b>	11 ± 0,5
<b>Nominal yield</b>	30 ÷ 50g/m <sup>2</sup>
<b>Environmental temperature</b>	min +10°C, max +30°C
<b>Dry to the touch</b>	1 hour with environmental temperature of 20°C
<b>Dry to handle</b>	48 hours with environmental temperature of 20°C
<b>VOC classification As per Dir. 2004/42/EC, Cat. A/I: Decorative effect coatings EU limit value: 300g/l (2007), 200g/l (2010)</b>	0 g/l of VOC if uncoloured

The information contained in this sheet has only informative value, as we cannot consider the specific conditions of each application.

Issued by:	Export Manager or External Institution	Approved by:	Export Manager		
	<b>Atova International</b> 2452 N Harlem, Elmwood Park, Il 60707 Phone: 708-452-9982; Fax 708-452-8331 <a href="mailto:info@paintandplasters.com">info@paintandplasters.com</a> <a href="http://www.paintandplasters.com">www.paintandplasters.com</a>	Document	<b>ST020ING</b>		
		Issue date	<b>24/10/05</b>		
		Revision	<b>06</b>		
		Revision date	<b>01/06/08</b>		
		Page 1 of 1			