



# TECHNICAL DATA SHEET

PRODUCT:

FOND FINE PRIMER

## DESCRIPTION

FOND FINE is a special clinging primer for mineral lime based products, based on acrylic polymers, natural fine quartz, inert charges and special additives. FOND FINE has a low content of VOC.

FOND FINE is a coarse primer, expressly formulated to adhere to all kind of surfaces.

Its particular rough structure eases the application of the exact quantity of product(in the first coat), in order to obtain the required thickness and a particularly glossy surface, with a high-quality final result of the covering.

The correct set up of the support is mandatory for a good result. As a consequence, if a primer coat is required, it's essential the use of the FOND FINE.

FOND FINE is suitable for a primer coat for indoor and outdoor surfaces.

Surfaces where is mandatory the use of FOND FINE primer:

## NEW SURFACE APPLICATION

SURFACE	PRELIMINARY TREATMENTS
Cement based building plaster	coat of fixative FOND FINE
Concrete	coat of fixative FOND FINE
Plasterboard	coat of fixative FOND FINE
Plaster	coat of fixative FOND FINE
Medium-density	coat of fixative FOND FINE

## OLD SURFACE APPLICATION

SURFACE	PRELIMINARY TREATMENTS
Washable paint	coat of fixative FOND FINE
Multicolor paint	coat of fixative FOND FINE
Glossy lime-based untreated finishing	good brushing and coat of fixative FOND FINE
Glossy lime based finishing with soap coating	good brushing and coat of fixative FOND FINE
Glossy lime based finishing with wax coating	good brushing and coat of fixative FOND FINE

The information contained in this sheet has only informative value, as we cannot consider the specific conditions of each application.

Issued by:	Export Manager or External Institution	Approved by:	Export Manager		
	Atova International 2452 N Harlem, Elmwood Park, IL 60707 Phone: 708-452-9982; Fax 708-452-8331 <a href="mailto:info@paintandplasters.com">info@paintandplasters.com</a> www.paintandplasters.com			Document	ST018ING
				Issue date	07/10/05
				Revision	06
				Revision date	21/05/07
					Page 1 of 2

PRODUCT:

FOND FINE

## APPLICATION

FOND FINE must be diluted with water at 30 ÷ 40%. Application tools are brush and roller.

## STORAGE

The product maintains its properties for a period of 24 months if protected from excessive heat and cold. The storage temperature must be included between +5°C and +30°C. Protect from frost.

## SAFETY GUIDELINES

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly with water. For more information consult the safety sheet.

## DISPOSAL

The product must be disposed in agreement with current regulations. Empty containers have to be sent to recycling plants.

## NOTES

Mix the product in the bucket also during the application to avoid sedimentation.

## TECHNICAL SPECIFICATIONS

Appearance	glossy mat slightly rough
Color	semi-transparent white
Dilution	30 ÷ 40% of water
Packaging	5 l net
Application tools	brush, roller
Specific weight	1,44 ± 0,08 Kg/l
Theoretical yield	0,150 ÷ 0,200 Kg/m <sup>2</sup> per coat
Coating thickness	0,10 ÷ 0,15 mm per coat
Application temperature	Min. temperature: +10°C (relative humidity below 85%) Max. temperature: +30°C (relative humidity below 85%)
Dry to the touch	2 hours with 20°C temperature
Dry to handle	24 hours with 20°C temperature
Dry to recoat	12 hours with 20°C temperature
Permeability to water vapour (Sd)	high
VOC classification As per Dir. 2004/42/EC, Cat. A/h: Binding primers EU limit value: 50g/l (2007), 30g/l (2010)	12 g/l of VOC if uncolored