

Marmorino Veneziano Puntinato

Black Dotted Lime Venetian Plaster Puntinato



Stucco Marmorino Puntinato is a blade-applied wall coating based on slaked lime putty finely filtered and seasoned for at least 6 months and on natural inert charges. Its environmental friendly formula is solvent free (0% VOC) and extremely low in chemical additives (less than 1,50% in total dry residue). Easy to apply, it has excellent filling power and resists aggression by moulds and bacteria. Marmorino Puntinato is suitable for decorative indoor wall surfaces. Perfectly stable over time, it ensures outstanding breathe through properties thanks to its excellent permeability to water vapour. In order to obtain the suitable supports it is necessary to prepare them correctly, applying a coat of primer Fondo Fine is a special clinging primer for mineral lime based products, based on acrylic polymers, natural fine quartz, inert charges and special additives. Fondo Fine has a low content of VOC.

Fondo Fine is a coarse primer, expressly formulated to adhere to all kind of surfaces. Its particular rough structure eases the application of the exact quantity of product (in the first coat), in order to obtain the required thickness and a particularly glossy surface, with a high-quality final result of the covering. The correct set up of the support is mandatory for a good result. As a consequence, if a primer coat is required, it's essential to use the primer. Fondo Dine is suitable for a primer coat for indoor and outdoor surfaces.

New Surface Application: building plasters, medium-density, concentrate, plasterboard, plaster—use coat of fixative fondo fine. **Old Surface Applications:** building plaster, tempera, breathable paint, glossy lime based untreated finishing, soap coating, wax coating, washable paint, multicolor paint.- use coat of fixative fondo fine. Marmorino Puntinato is ready to use. Any water present on the surface is considered normal, and should be completely removed before using. For tinting, before adding the chosen color tint reduce the viscosity of the product by mixing it with a special rotor drill. Then add the amount of color tint indicated and blend until the color is perfectly even. Let the colored product rest for 12 hours before starting the application cycle.

FIRST COAT Consumption: approximately 1.000 ÷ 1.200 g/m² It should be applied evenly, being careful to create an even, flat surface.

SECOND COAT AND POLISHING Consumption: approximately 200 ÷ 300 g/m²

Proceed when the first coat is dry, apply the material working with a steel blade sloping at 45° to show the dots below. **THIRD COAT AND POLISHING** Consumption: approximately 80 ÷ 100 g/m²

Proceed when the second coat is dry. In order to obtain an even color, we suggest to use the same colored bucket for the whole surface. Polishing is performed during the drying stage. The gloss is the result of pressing the steel blade to the coating surface.

Coverage: 12-15 sqf/ quart Sizes: 1 quart 1 gallon, 2 gallons, 4 gallons,

ENVIRONMENTAL CONDITIONS OF APPLICATION

The environmental temperature must be included between +50 F and +86 with relative humidity lower than 85%, also in the 24 hours following the application. **STORAGE:**The product maintains its properties for a period of 24 months if protected from excessive heat and cold. Storage temperature must be included between +41 F and +86F. Protect from frost. **SAFETY GUIDELINES:**The lime makes this product caustic. Avoid contact with skin and eyes. If contact occurs, rinse thoroughly with water. For more information consult the safety sheet. Keep this product away from children. **DISPOSAL:**The product must be disposed in agreement with current regulations. Empty containers to be sent to recycling plants.

This Information is based on our best technical and practical knowledge. However, since the actual conditions in which the products are used beyond our direct control, we provide no guarantee as to effectiveness of the advice and suggestions contained herein. If in doubt, it is advisable to conduct preliminary tests and/or call our technical service. For more information, please call: 1-866-452-9982 www.paintandplasters.com



- R41— Risk of serious damage to eye
 - S2— Keep out for the reach of children
 - S25-Avoid contacts with eyes
 - S26-In case in contact with eyes, rinse immediately with plenty of water and seek medical advice.
 - S36/39-wear suitable protective clothing and eye face protections
 - S46-If swallowed, seek medical advice immediately and show this container or label.
- Danger labeling under directives 67/548CEE and 1999/45/CEE and following amendments and adjustments